
# Rinnai

### **Gas Boosted Solar**



#### **Rinnai Gas Solar Hot Water Systems**

## Rinnai

#### **Close Coupled**

A close coupled system is where the Storage Cylinder and the Solar Collectors are coupled together and the installation is on the roof

Rinnai Close Coupled Solar Systems use the thermo-syphoning principle (i.e. hot water rises because it is less dense) to circulate the water through the Collectors and then to the Storage Cylinder without the need for a pump.

Supplementary heating, more commonly referred to as the gas booster, is provided if insufficient heat is available from the sun (such as during cloudy or rainy weather or during winter months).

#### **Features**

- · Low heat loss due to greater insulation
- · Supplied standard in Platinum Grey or Silver Prestige colour
- Wide range of Colorbond® colours available. Ask your Rinnai Solar consultant for the full colour selection
- Continuous Flow Gas Booster same technology as the Rinnai INFINITY and available in four sizes



- Technically very efficient, economical to install and low maintenance
- No recirculating pumps and pipe runs reducing heat losses and improving running efficiencies
- No electricity required to operate pumps to recirculate the water through the collectors
- Space saving in that it eliminates the need for a storage tank at ground level – ideal for courtyard homes or small blocks

#### **Split Systems**

A split system is where the Storage Cylinder and the Solar Collectors are split and installed separately.

A solar control unit ensures the water circulates via a pump between the Solar Collectors and the Storage Cylinder. This transfers heat from the Collectors to the water in the cylinder if enough heat is available from the sun. A Rinnai gas booster mounted either on a wall or on the side of the tank will boost the solar heated water if necessary.

#### **Features**

- Rinnai Prestige improved insulation levels
- Streamlined appearance minimal impact on the aesthetics of your roofline with only the Collectors visible
- Continuous Flow Gas Booster same technology as the Rinnai INFINITY and available in four sizes

#### **Benefits**

- Easy installation on rooves
- Split Systems do not require reinforcement of the roof structure, as the weight associated with water storage is at ground level
- Split System Cylinder can be installed internally or externally
- · Collectors and the Cylinder do not need to be installed at the same time
- Gas booster ensures that you will never run out of hot water









#### **Solar Collectors**



#### **Excelsior Solar Collectors**

- Highly efficient all copper Collector with a selective surface maximising energy absorption from the sun
- 10 Riser tubes per panel for effective transfer of the solar energy to heat the water
- Full aluminium casing for corrosion resistance
- Also available as Frost Tolerant (FTC) model for temperatures down to -6°C

### E-Frost Solar Collectors

- Exclusive Rinnai patented technology delivering true protection against frost and freezing
- Suitable and warranted for operating temperatures down to -12°C
- Designed for Rinnai Split System solar hot water heaters
  not compatible with Close Coupled Systems
- Mandatory installation in areas nominated by Post Code in NSW,
  VIC & ACT. Ask your Rinnai Solar Specialist or see rinnai.com.au





#### **Solar Rebates**

#### **Government Rebates**

The Australian Greenhouse Office awards Small Scale Technology Certificates (STCs) formerly known as RECs, according to how much energy each Rinnai Solar system saves compared with a conventional electric water heater. The Federal Government legislation states that STCs are applicable when a solar system is installed in a new home or replaces an existing hot water system.

#### **STCs and Rinnai Solar Systems**

Rinnai offer the following popular combinations, however, if your particular system is not shown, please ask your Rinnai Solar Specialist who can further advise.

Rinnai Prestige Gas Solar Systems		Cylinder Size	Gas Booster	No of Collectors	STCs Zones <sup>(1)</sup> Excelsior & Excelsior FTC Collectors				STCs Zones <sup>(1)</sup> E-Frost Collectors			
					1	2	3	4	1	2	3	4
Split System Gas	System B	250L	S20	2	36	41	36	31	27	30	28	24
	System C	250L	S26	2	36	41	36	31	27	30	28	24
	System D	315L	S26	2	36	40	35	31	26	29	27	24
	System E	315L	S26	3	41	44	43	37	37	41	37	32
Close Coupled Gas	System L	180L	S20	1	24	28	24	21	Not available for use with			
	System M	330L	S26	2	39	43	39	34	Close Coupled Systems			

(1) STCs are subject to change. See www.cleanenergyregulator.gov.au for conditions and qualifications.



You may also be eligible for State Government rebates. To assist with the eligibility and calculation of rebates, we have produced an online calculator. Simply go to rinnai.com.au and click on the Solar Rebate Estimator icon.

#### **The Environment**

Gas is one of the most greenhouse friendly fuel sources available. By choosing a Rinnai gas boosted Solar System you can make a difference! Gas Boosted Solar hot water has substantial benefits and assists with the reduction of our carbon footprint. Solar systems are awarded Small Scale Technology Certificates (STCs) based on measured environmental savings. Even electric boosted systems show considerable savings and are awarded high STCs. Rinnai systems have amongst the highest STCs in the industry.



Rinnai also offer Electric Systems as an alternative where Gas is not available. Ask your Rinnai Solar Specialist about the benefits of a Gas boosted system.

Solar Hot Water Warranty		Continuous Flow Models S20 and models convert	mpatible w Water Heaters d S26 and other red by Rinnai for ications <sup>(1) (3)</sup>	<b>Storage Cylinder</b> Prestige Stainless Steel Range	Solar Collectors Excelsior & E-Frost	Components (2) (5)	
		Heat Exchanger	All other components				
Domestic Use	Parts	10 Years	3 Years <sup>(4)</sup>	10 Years	7 Years	1 Year (4) (5)	
	Labour	3 Years 3 Years		3 Years	1 Year	1 Year	
Commercial Use	Parts	5 Years	1 Year	5 Years	5 years	1 Year	
	Labour 1 Year		1 Year	1 Year	1 Year	1 Year	

<sup>(1)</sup> The continuous flow models in this column are suitable only for solar hot water applications. Any failure or service issue when installed in a non solar hot water application is not covered by warranty. (2) Components include pumps, system controllers, sensors, thermostats, valves, electric heating elements and anodes where applicable. (3) Some other models can be converted for solar applications by Rinnai by order request. (4) For Victorian installations only - 5 year warranty on the solar circulating pump, solar controller and components within the continuous flow water heater in order to comply with State legislation where applicable. (5) For Queensland installations only - 2 Year warranty on the solar circulating pump in order to comply with State legislation where applicable.

#### Please note:

For full definitions of Domestic and Commercial use, along with the full warranty conditions and exclusions, please refer to **rinnai.com.au** Rinnai Australia Pty Ltd reserves the right to make modifications and change specifications without notice.



#### **RINNAI AUSTRALIA PTY. LTD**

ABN 74 005 138 769

10-11 Walker Street Braeside VIC 3195 For further information visit www.rinnai.com.au or call 1300 555 545 **Dealer Details**